



HEADY24



APPLICATION

1 or 2 actuators for swing gates

CONTROL UNIT POWER SUPPLY

230 Vac

MOTORS POWER SUPPLY

24 Vdc 60W + 60W

MAIN FUNCTIONS

Integrated LCD display | Integrated 433.92 MHz 64-code radio receiver with 3 encoding systems (Advanced Rolling Code, Rolling Code, Fixed Code) | Removable terminal boards | Automatic and semi-automatic logic | Separate limit switch inputs for each motor | Pedestrian, step by step and stop inputs | Separate photocell inputs in opening-closing and in closing phases | Outputs for configuration as gate open indicator, second radio channel or photocell testing | Autosetting of operating parameters | Separate electronic torque adjustment for each motor | Anti-crushing safety thanks to amperometric detection and encoder management | Separate adjustable slow-downs for each motor | Advantouch system to configure parameters and manage radio transmitters | Number of maneuvers | Programming access password | Maintenance warning



DU.V96
12 Vac/dc vertical electric lock, supplied with counterplate. Permits internal/external release.



DU.V90
12 Vac/dc horizontal electric lock, supplied with counterplate. Permits internal/external release.



DU.9990
Covering plate for DU.V90.



L.BY
Control board for electric lock 12/24 Vdc.



BRAINY24.CB
Accessory with CBY.24V battery charger, 1.2 Ah batteries and support bracket.

