

## ARCA 403021



Sample photo

Order symbol: ARCA 403021  
Product nbr: 8120007  
Description: Cabinet, PC  
Remarks: 2-point locking

EAN: 6418074079183  
El. number:  
Finland: 3423054  
Electric No. Denmark: 8212091058  
Electric No. Sweden: 2500114

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:		Length	Width	Height	Rating:
mm:		400	300	210	Ingress Protection (EN 60529): IP66
inch:		15.7	11.8	8.3	Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C
Materials:					Electrical insulation: Totally insulated
Material:		Polycarbonate			Halogen free (DIN/VDE 0472, Part 815): 1
Base colour:		RAL 7035 -light grey			UV resistance: UL 508
Cover colour:		RAL 7035 -light grey			Flammability Rating: UL 94 5VA
Gasket material:		Polyurethane			Glow Wire Test (IEC 695-2-1) °C: 960
Temperatures:					Certificates:
Temperature °C (short term):		-40 ... 120 °C			SGS Fimko
Temperature °C (continuous):		-40 ... 80 °C			Gost R
Temperature °F (short term):		-40 ... 250 °F			
Temperature °F (continuous):		-40 ... 175 °F			

